

DSEEXTRA[®] BATTERY CHARGERS AND EXPANSION MODULES.

DSE860/DSE865

SINGLE-SET COMMUNICATIONS DEVICES



The DSE860 and DSE865 are communications devices that allow you to monitor single generating sets over a LAN (network) or WAN (internet) connection. The devices include software that is used to assign a TCP/IP address to a COM Port on a PC. This COM port is then selected by the user in the standard PC software of the DSE module being used. Once this COM port has been selected then the user can communicate directly with the control module from their PC.

If the device needs to be seen over the internet the assigned IP address has to be configured to be visible to the outside world. Once this has been done the module can be communicated with from any remote location that has internet connectivity.

The devices have been designed to work with the DSE73xx and DSE75xx control modules.

The devices also include LED indicators that show the operation and connection status at all times. Different light patterns indicate a range of status conditions.

FEATURES

- Can be used over an internal network and the internet
- LED status indicators on the devices aid fault finding
- TCP/IP software is extremely easy to use
- Devices automatically reconnect in the event of loss of communication
- Fully customer configurable settings
- DIN rail mounting

BENEFITS

- Works with the DSE73xx and 75xx control modules
- Generic connectors for simple plug-in operation
- DIN rail mounting allows devices to be installed securely within a panel
- Allows users from different locations to view generator status

OPERATION

A simple PC Windows based application enables the user to assign a TCP/IP address to a COM port. The modules standard PC software then connects to the control module through the selected port. To use the product over the internet, the IP address given to the DSE860/865 must be made visible to the outside world.

SPECIFICATION

DC OUTPUT

8V to 35V DC Continuous

ETHERNET CONNECTION

10Base-T or 100Base-TX (IEEE 802.3). RJ45 connector

COVER MATERIAL

Grey/Black plastic, LEXAN 940, self extinguishing acc. To UL94-V0

MOUNTING OPTION

DIN rail (EN50022)

DIMENSIONS

86mm x 35mm x 57mm
3.4" x 1.4" x 2.2"

ENVIRONMENTAL TESTING STANDARDS

ELECTRO MAGNETIC CAPABILITY

BS EN 61000-6-2
EMC Generic Emission Standard for the Industrial Environment
BS EN 61000-6-4
EMC Generic Emission Standard for the Industrial Environment

TEMPERATURE

BS EN 60068-2-2
Test Ab to +70°C 60067-2-2 Hot
Test Ab to -30°C 60068-2-1 Cold

VIBRATION

BS EN 60068-2-6
Ten sweeps in each of three major axes
5Hz to 8Hz @ +/-7.5mm, 8Hz to 500Hz @ 2gn

HUMIDITY

BS 2011 part 2.1 60068-2-30
Test Cb Ob Cyclic
93% RH @ 40°C for 48 hours

SHOCK

BS EN 60068-2-27
Three shocks in each of three major axes
15gn in 11ms

DEEP SEA ELECTRONICS PLC

Highfield House
 Hunmanby Industrial Estate
 Hunmanby, North Yorkshire
 YO14 0PH England

TELEPHONE

+44 (0)1723 890099

FACSIMILE

+44 (0)1723 893303

EMAIL

sales@deepseapl.com

WEBSITE

www.deepseapl.com

Registered in England & Wales No.01319649

VAT No.316923457

DEEP SEA ELECTRONICS INC

3230 Williams Avenue
 Rockford
 IL 61101-2668 USA

TELEPHONE

+1 (815) 316 8706

FACSIMILE

+1 (815) 316 8708

EMAIL


sales@deepseausa.com

WEBSITE

www.deepseausa.com



DIAGRAM

**RELATED MATERIALS**

TITLE	PART NO'S
DSE860 865 Manual	057-099
DSE7310/20 Data Sheet	055-051
DSE7510 Data Sheet	055-065
DSE7520 Data Sheet	055-066
DSE7560 Data Sheet	055-067
DSE7310/20 Manual	057-074
DSE7510 Manual	057-088
DSE7520 Manual	057-089
DSE7560 Manual	057-090

DEEP SEA ELECTRONICS PLC maintains a policy of continuous development and reserves the right to change the details shown on this data sheet without prior notice. The contents are intended for guidance only.

This data sheet is printed on 9lives 55 Silk, which is produced with 55% recycled fibre from both pre and post-consumer sources, together with 45% virgin ECF fibre.

