#### **Specification sheet**



# QSB5-G5

EU Stage IIIA / EPA Tier 3 / TA Luft Compliant



#### **Description**

The QSB5 incorporates the latest diesel engine technology, including a high pressure common rail fuel system for greater fuel efficiency, lower noise and reduced emissions.

#### **Features**

**Full-Authority Electronic Controls** - Optimize engine operation and deliver critical information for controlling costs, reducing maintenance and seamless integration with other components.

**Holset HX35 Wastegated Turbo** - Wastegated design optimizes transient response.

Low-Maintenance Fuel Filter Assembly - The fuel filter incorporates an integral water separator and water-in-fuel sensor; 500-hour filter life with easy top-load replacement using standard Fleetguard® filters.

**Coolpac Integrated Design** - Products are supplied complete with cooling package and air cleaner kit for a complete power package. Each component has been specifically developed and rigorously tested for G-Drive products, ensuring high performance, durability and reliability.

**Service and Support** - G-Drive products are backed by an uncompromising level of technical support and after sales service, delivered through a world class service network.



This engine has been designed in facilities certified to ISO9001 and manufactured in facilities certified to ISO9001 or ISO9002.



## **1500 rpm (50 Hz ratings)**

Gross engine output		Net engine output		Typical generator set output							
Standby	Prime	Base	Standby	Prime	Base	Standb	y (ESP)	Prime	(PRP)	Base	(COP)
kWm/BHP			kWm/BHP		kWe	kVA	kWe	kVA	kWe	kVA	
113/151	97/130	88/118	105/141	90/121	81/109	88	110	80	100	76	94

## **1800 rpm (60 Hz ratings)**

Gross engine output			Net engine output		Typical generator set output						
Standby	Prime	Base	Standby	Prime	Base	Standb	y (ESP)	Prime	(PRP)	Base	(COP)
kWm/BHP			kWm/BHP		kWe	kVA	kWe	kVA	kWe	kVA	
131/176	113/152	104/139	119/160	101/135	93/125	100	125	90	113	87	108

#### **General engine data**

Туре	4 cycle, in-line, 4 cylinder diesel
Bore mm	107 mm (4.21 in.)
Stroke mm	124 mm (4.88 in.)
Displacement litre	4.5 litre (275 in. <sup>3</sup> )
Cylinder block	Cast iron, 4 cylinder
Battery charging alternator	100 amps
Starting voltage	12 volt, negative ground
Fuel system	Direct injection
Fuel filter	Dual spin-on fuel filters with water separator
Lube oil filter type(s)	Spin-on full flow filter
Lube oil capacity (I)	12.2
Flywheel dimensions	SAE3
* @ 40 11.0	·

<sup>\*\* @ 13</sup> mm H<sub>2</sub>0

#### Fuel consumption 1500 (50 Hz)

%	kWm	ВНР	L/ph	g/kWh			
Standby Power							
100	113	152	29	7.5			
Prime Pow	Prime Power						
100	97	130	25	6.6			
75	73	98	20	5.3			
50	48	65	13	3.5			
25	24	33	7	1.9			
Continuou	Continuous Power						
100	88	118	24	6.3			

#### Fuel consumption 1800 (60 Hz)

%	kWm	ВНР	L/ph	g/kWh		
Standby Power						
100	131	176	34	8.9		
Prime Power						
100	113	152	29	7.7		
75	85	114	24	6.4		
50	57	76	16	4.3		
25	28	38	9	2.4		
Continuous Power						
100	104	139	27	7.2		

Our energy working for you.  $^{\scriptscriptstyle{\mathsf{M}}}$ 

## Weights and dimensions (Engine only)

Length	Width	Height	Weight (dry)	
mm	mm	mm	kg	
821	739	982		

#### **Ratings definitions**

rtainige acimination			
Emergency Standby Power (ESP):	Limited-Time Running Power (LTP):	Prime Power (PRP):	Base Load (Continuous) Power (COP):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789, DIN6271 and BS 5514.



For more information contact your local Cummins distributor or visit power.cummins.com

