




QSB7-G5

EU Stage IIIA / EPA Tier 3



Description

The QSB7 incorporates the latest diesel engine technology, including a high pressure common rail fuel system for greater fuel efficiency, lower noise and reduced emissions.

Features

Full-Authority Electronic Controls - Optimize engine operation and deliver critical information for controlling costs, reducing maintenance and seamless integration with other components.

Holset HX35 Wastegated Turbo - Wastegated design optimizes transient response.

Low-Maintenance Fuel Filter Assembly - The fuel filter incorporates an integral water separator and water-in-fuel sensor; 500-hour filter life with easy top-load replacement using standard Fleetguard® filters.

Coolpac Integrated Design - Products are supplied complete with cooling package and air cleaner kit for a complete power package. Each component has been specifically developed and rigorously tested for G-Drive products, ensuring high performance, durability and reliability.

Service and Support - G-Drive products are backed by an uncompromising level of technical support and after sales service, delivered through a world class service network.



This equipment is EU RoHS compliant and has been built to comply with CE certification requirement.



This engine has been designed in facilities certified to ISO9001 and manufactured in facilities certified to ISO9001 or ISO9002.

1500 rpm (50 Hz ratings)

Gross engine output			Net engine output			Typical generator set output					
Standby	Prime	Base	Standby	Prime	Base	Standby (ESP)		Prime (PRP)		Base (COP)	
kWm/BHP			kWm/BHP			kWe	kVA	kWe	kVA	kWe	kVA
213/285	182/224	152/204	197/264	168/225	138/185	176	220	160	200	128	160

1800 rpm (60 Hz ratings)

Gross engine output			Net engine output			Typical generator set output					
Standby	Prime	Base	Standby	Prime	Base	Standby (ESP)		Prime (PRP)		Base (COP)	
kWm/BHP			kWm/BHP			kWe	kVA	kWe	kVA	kWe	kVA
242/324	208/279	164/220	225/302	194/260	150/201	200	250	180	225	140	175

General engine data

Type	4 cycle, in-line, 6 cylinder diesel
Bore mm	107 mm (4.21 in.)
Stroke mm	124 mm (4.88 in.)
Displacement litre	6.69 litre (275 in. ³)
Cylinder block	Cast iron, 6 cylinder
Battery charging alternator	100 amps
Starting voltage	12 volt, negative ground
Fuel system	Direct injection
Fuel filter	Spin-on fuel filters with water separator
Lube oil filter type(s)	Spin-on full flow filter
Lube oil capacity (l)	18.9
Flywheel dimensions	SAE2

Coolpac performance data

Cooling system design	Air-air Charge Cooled
Coolant ratio	50% ethylene glycol; 50% water
Coolant capacity (l)	26
Limiting ambient temp.** (°C)	60 (50Hz); 60 (60Hz)
Fan power (kWm)	6.9 (50Hz); 12.7 (60Hz)
Cooling system air flow (m ³ /s)**	5.3 (50Hz); 6.32 (60Hz)
Air cleaner type	Light duty dry replaceable element with restriction indicator

** @ 13mm H2O

Fuel consumption 1500 (50 Hz)

%	kWm	BHP	L/ph	g/kWh
Standby Power				
100	213	285	51	13.4
Prime Power				
100	182	244	45	11.9
75	137	183	36	9.5
50	91	122	26	6.9
25	46	61	13	3.4
Continuous Power				
100	152	204	40	10.5

Fuel Consumption 1800 (60Hz)

%	kWm	BHP	L/ph	g/kWh
Standby Power				
100	242	324	59	15.5
Prime Power				
100	208	279	50	13.3
75	156	209	40	10.6
50	104	140	30	7.8
25	52	70	15	4
Continuous Power				
100	164	220	42	11

Weights and dimensions

Length mm	Width mm	Height mm	Weight (dry) kg
1688	862	1190	585

Ratings definitions

Emergency Standby Power (ESP):	Limited-Time Running Power (LTP):	Prime Power (PRP):	Base Load (Continuous) Power (COP):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789, DIN6271 and BS 5514.



For more information contact your local Cummins distributor
or visit power.cummins.com

Our energy working for you.™

